



## FEATURES

- Rugged compressor with cast iron cylinders
- "V" design minimizes vibration, improves cooling and extends compressor life
- Individual and removable cylinders for smoother and cooler operation
- Heavy duty pressure switch has on/off control
- Thermally protected 5 HP and 7.5 HP single phase, three phase 208/230/460 volt or three phase 575 volt electric motors
- Metal air filters with "Auto Drop" feature
- Convenient oil drain on front of unit
- 80 gallon ASME registered tank, 200 PSIG rating
- Easy view oil sight gauge
- High efficiency reed valves for maximum performance
- Efficient heat removal from pulley-fan for cooler running and longer life
- Sturdy metal belt guard
- Outlet valve included

5\*80V2-MS

**200**  
PSI UNIT



**18.5**  
**CFM**  
@ 100 PSI

7\*80V2-MS

**200**  
PSI UNIT



**24.6**  
**CFM**  
@ 100 PSI

\*Voltage to be specified (1-single phase, 3- three phase 208/230/460V, or 5 -three phase 575V)

MODEL	HP	CFM@ 100 PSI	MAXIMUM RATED PSI	RECEIVER CAPACITY	MOTOR	DIMENSIONS L-W-H (ins)	WEIGHT (lbs)
5*80V2-MS	5.0	18.5	200	80 Gal	*208/230/ 460 or 575	35-24-69	450
7180V2-MS	7.5	24.6	200	80 Gal	208/230 V	35-24-69	450
7*80V2-CS	7.5	24.6	200	80 Gal	*208/230/ 460 or 575	35-24-69	450

1-877-249-3600

www.lyncopro.com