

Cold (HOT*) Water: Electric Powered – Stationary or Portable

The **CW Series** is a unique washer with hot water inlet capabilities that saves you time and money. Pressure clean thoroughly using your existing hot-water supply, up to 165°F. The CW's versatile design allows it to be wall-mounted, stationary or portable depending on the cleaning task or application. The adjustable pressure wand and auto start/time delay shutdown features give the operator total control from the wand – no traveling back and forth to the unit to adjust the pressure or turn switches. The heavy-duty industrial components, stainless steel frame/cover, and a low rpm belt drive pump for long lasting performance.

PRESSURE	3000 psi
FLOW CAPACITY	3.9 gpm
POWER / ENGINE	8.0 hp
VOLTS / PHASE / AMPS	Dual rated for 208v or 230v / 1ph, 36amp
CONTROLS / SWITCHES	Hour meter, lighted on/off switch, soap control
PUMP	General Pump, triplex ceramic plunger
POWER DRIVE	V-Belt drive with EZ Align™ pump rail
PRESSURE CONTROL	Adjustable pressure unloader, 24v adjustable timer with 7 to 300 second control
WATER SUPPLY	Pressure feed from garden hose
WATER TEMPERATURE	Inlet water temperature up to 165°F from hot water source
SOAP INJECTION	Downstream soap injection included, inlet soap injection option available
PRESSURE HOSE	3/8" x 50' 3000psi wire braided hose
GUN / WAND	48" molded insulator, adj. pressure wand with quick coupler
NOZZLE	#4 x 15°, 25°, 40°
FRAME CONSTRUCTION	Stainless steel frame and removable cover
WHEELS	Optional wheel / handle kit
DIMENSIONS (LxWxH)	29" x 21" x 15" (31" x 31" x 20" with wheels, plus handle height)
NET WEIGHT	180#

Specifications subject to change without notification and may vary due to ambient conditions.

*** CW Series accepts water from hot water heater or other hot water source up to 165°F**

Featuring:

- ✓ **All Stainless Construction** is corrosion resistant and sanitary, ideal for use in food processing or medical facilities
- ✓ **EZ Align™** pump rail system for simple belt adjustments
- ✓ **Auto ON/Off** with time delay shutdown saves time & effort

Options...

Wall mount brackets, sideways mount (ACW09), Wall mount hose reels (AR188), Wheel/handle kit (AHS15), Float tank/inlet soap injection option (WT0CW – not compatible with high temp options or 8gpm models), Multi station outlets (ACW20), Wall mount remote options (AEN35 or AEN22)



Shown with optional wheel / handle kit

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY:

	Lynco Products Inc # 114, 1220 - 28 STREET N.E CALGARY, AB T2A 6A2 403-250-3600 / 1-877-249-3600 sales@lyncoopro.com / www.lyncoopro.com
---	---