

HYDRO TEK

CLEANING EQUIPMENT MFG.

2353 Almond Ave. Redlands, CA 92374
phone 800.274.9376 or 1.909.799.9222
www.hydrotek.us fax 909.799.9888

HD10003E1G

HD Series – Pressure Steamer

Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The **HD Series** offers rugged, dependable, affordable washing. It features a heavy-duty stainless steel frame, handles, panels and coil protection – offering superior corrosion resistance, as well as four pneumatic wheels. Panel mounted temperature control offers the benefits of high pressure cleaning with water temperature from cold through full steam settings. Panel mounted controls allow the operator to vary the mixture of soap, or other additives, which can be delivered at full pressure – for optimal cleaning effectiveness. High efficiency coil and large capacity diesel fuel tank offer up to 8 hours of operation between refueling. Ideal for farm and agricultural applications, auto repair shops, and wherever sanitizing and degreasing are needed.

PRESSURE	1000psi
FLOW CAPACITY	3.0gpm
OUTLET TEMP	Adj. to 250°F (140°F Rise)
POWER/ENGINE	2.0 HP
VOLTS/PHASE/AMPS	115v / 1ph / 20a
POWER CORD	35' cord with Ground Fault Circuit Interrupter for additional safety
CONTROLS/SWITCHES	Lighted rocker switches, panel mounted soap control, adjustable thermostat
PUMP	General Pump, Forged brass manifold, Triplex Ceramic Plunger
POWER DRIVE	V-Belt Drive with EZ Align™ pump rail, Low RPM – Cooler, Quieter
PRESSURE CONTROL	Adjustable Pressure Unloader, Safety Relief Valve, Burst Disc, By-Pass-Cool System
WATER SUPPLY	4 Gal Float Tank, Double Inlet Filtration
PRESSURE HOSE	3/8" x 50' Steel Wire Braid Hose, 3000 PSI, 250°F Rated
GUN / WAND	Insulated Shut Off Gun / 36" Wand w/Nozzle Quick Connector
SOAP INJECTION	Inlet soap/chemical injection, Injects Soap At Full Pressure
NOZZLE	#5.5(15°,40°) #4.5(25°)
BURNER COIL	Spiralast™ robotically fused 1/2" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation
BURNER/POWER	Beckett Oil Fired, Automatic Ignition, Forced Draft, Fuel Filter w/ Water Separator
BURNER FUEL / CAP	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gal. capacity – 294,000 Btu input
CONSTRUCTION	All Stainless: frame, panels, coil wrap, and double wall coil end caps
WHEELS	4) wheels installed
NET WEIGHT / DIMS	297# 47x29x36

*Specifications subject to change without notification and may vary due to ambient conditions.

Featuring:

- ✓ **Efficient Heating:** Schedule 80 coil is stainless steel wrapped and insulated to make efficient use of the burner heat.
- ✓ **Flexible, Effective Cleaning:** Adjustable temperature with steam setting and soap/chemical injection delivers more cleaning power over a wide range of applications.
- ✓ **Compact and Portable:** Wheels included. Easily moved to wherever you need to clean



Options...

Stainless Steel Hose Reel (AR004)

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____



Lynco Products Inc
114, 1220 - 28 STREET N.E
CALGARY, AB T2A 6A2
403-250-3600 / 1-877-249-3600
sales@lyncoopro.com / www.lyncoopro.com



©2013 Hydro Tek (rev 3/15 HD10003E1G)