

# HYDRO TEK

CLEANING EQUIPMENT MFG.

2353 Almond Ave. Redlands, CA 92374  
phone 800.274.9376 or 1.909.799.9222  
www.hydrotek.us fax 909.799.9888

# HP22005E2

## HP Series – Pressure Steamer

### Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The **HP Series** combines the cleaning power of high pressure and high water flow with the grease cutting effectiveness of hot water. Simply pull the trigger on the spray gun, and instantly the machine turns itself on and delivers high pressure cleaning power. The temperature can be adjusted to cold, hot, or steam for any cleaning application. The portable design and stainless steel construction offers years of trouble free service and cleaning performance anywhere electrical power is available.

<b>PRESSURE</b>	2200psi
<b>FLOW CAPACITY</b>	4.3gpm
<b>OUTLET TEMP</b>	Adjustable up to 250°F (150°F rise)
<b>POWER / ENGINE</b>	6.5hp
<b>VOLTS/PHASE/AMPS</b>	230v / 1ph / 27amp
<b>CONTROLS/SWITCHES</b>	Lighted on/off and lighted burner switch, thermostat, hour meter
<b>PUMP</b>	Cat Pump, Oil Bath, Triplex Ceramic Plunger, Brass Head, Stainless Steel Valves
<b>POWER DRIVE</b>	V Belt drive
<b>PRESSURE CONTROL</b>	Adjustable pressure unloader and wand, safety relief valve, safety burst disc
<b>WATER SUPPLY</b>	3-1/2 gal. float tank
<b>PRESSURE HOSE</b>	3/8" x 50' 4000psi Rated
<b>SOAP INJECTION</b>	Inlet chemical injection, injects at full pressure
<b>GUN / WAND</b>	48" molded insulator, adj. pressure wand with quick coupler
<b>NOZZLE</b>	#5.5 ( 15°, 40°) #4.5( 25° Steam)
<b>BURNER COIL</b>	Spiralast™ robotically fused 1/2" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation
<b>BURNER / POWER</b>	Oil Fired, Forced Draft, Automatic Ignition, Fuel Solenoid, Fuel Filter with Water Separator
<b>BURNER FUEL / CAP</b>	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gallon capacity– 372,400 Btu input
<b>CONSTRUCTION</b>	All Stainless: frame, panels, coil wrap, and double wall coil end caps
<b>WHEELS</b>	4) 13" tires installed
<b>NET WEIGHT / DIM</b>	470#, 46"x29"x39"

\* Specifications subject to change without notification and may vary due to ambient conditions

### Featuring:

- ✓ **Performance:** High heating ability and high flow increases cleaning speed and power
- ✓ **Portability:** Compact design for versatility and maneuverability.
- ✓ **Durability:** All Stainless steel construction and panels for lifetime corrosion resistance
- ✓ **Efficient:** High output diesel burner system offers clean burning and continuous hot water.
- ✓ **Convenient:** E.T.S. Electronic Trigger Start, 60 second delay Auto Off avoids risk of pump overheating and expensive thermal damage. Also features adjustable pressure at the wand

### Options...

Hose Reel (AR189), Wet Sandblaster, Downstream injection kit



HP shown with hose reel

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_



**Lynco** Products Inc  
# 114, 1220 - 28 STREET N.E  
CALGARY, AB T2A 6A2  
403-250-3600 / 1-877-249-3600  
sales@lyncoopro.com / www.lyncoopro.com