

TRAILER MOUNTED TRASH PUMPS

Outstanding Features

- Silicon Carbide Mechanical Seals
- Stainless Steel Impellers
- Solids Handling up to 3" in Diameter
- Easy to Remove Clean Out Cover
- Unique Pump End One Man Slide Mechanism
Allows Pump Service without Removing Hoses
- Engines with Electric Start and Low Oil Shut Off
- Maximum Liquid Temperature of 180 °F
- Tools Included for Pump Service
- D.O.T. Approved Trailer Standard
(See your State and Local Codes for Registration)



Lynco Lynco Products Inc
 # 114, 1220 - 28 STREET N.E
 CALGARY, AB T2A 6A2
 403-250-3600 / 1-877-249-3600
 sales@lynco.com / www.lynco.com

KTH-150

KTD-150

	KTH-150	KTD-150
Suction, Discharge Size	6" NPT	6" NPT
Maximum Output (GPM)	1000	1000
Maximum Discharge Head (ft)	98	98
Maximum Suction Lift (ft)	26	26
Maximum Pressure (Psi)	40	40
Engine Model	HONDA GX670	YANMAR 3TNM72
Engine Displacement (cc)	670	904
Engine Horse Power	23	23
Fuel Tank Capacity (Gal)	20	20
Full Load Run Time (hrs)	9	12
Fuel Type	Gasoline	Diesel
Packaged Weight (Lbs)	1000	1250
Packaged Dimensions (LxWxH)	77"x55"x65"	77"x55"x65"

