www.hydrotek.us fax 909.799.9888

SC35005VC

SC Series - Mobile Wash Skid

Hot / Cold Water - Self Contained: Diesel Heated, Gas Engine

The **SC Series** is a high output hot mobile wash skid with serious cleaning power. It was designed to withstand the daily use by professionals who rely on its dependability to make a living. Its high impact power enables it to handle just about any size cleaning task with ease and without the need for an outside power source. The SC Series is powered by industrial engines, hi torque–low RPM belt driven pumps and reliable 110v burner system with a 2.9Kw generator, providing power for running a water recycling system or other accessories. If portability is needed add a wheel kit or mount on a trailer, truck bed or tank skid.

PRESSURE FLOW CAPACITY 4.5gpm OUTLET TEMP Adjustable thermostat to 250°F (140°F Rise) POWER/ENGINE 570cc Vanguard ENGINE FUEL/CAP Unleaded gasoline, 8 gal CONTROLS/SWITCHES Adjustable thermostat, lighted burner control switch, optional hour meter available PUMP Cat Pump POWER DRIVE V-Belt Drive with EZ Align™ pump rail, stainless belt guard
OUTLET TEMP Adjustable thermostat to 250°F (140°F Rise) POWER/ENGINE 570cc Vanguard ENGINE FUEL/CAP Unleaded gasoline, 8 gal CONTROLS/SWITCHES Adjustable thermostat, lighted burner control switch, optional hour meter available PUMP Cat Pump
POWER/ENGINE ENGINE FUEL/CAP Unleaded gasoline, 8 gal CONTROLS/SWITCHES Adjustable thermostat, lighted burner control switch, optional hour meter available PUMP Cat Pump
ENGINE FUEL/CAP Unleaded gasoline, 8 gal CONTROLS/SWITCHES Adjustable thermostat, lighted burner control switch, optional hour meter available PUMP Cat Pump
CONTROLS/SWITCHES Adjustable thermostat, lighted burner control switch, optional hour meter available PUMP Cat Pump
PUMP Cat Pump
POWER DRIVE V-Belt Drive with EZ Align™ pump rail, stainless belt guard
PRESSURE CONTROL Unloader valve, Industrial fittings, Safety burst disc, Pressure relief valve
WATER SUPPLY Pressure feed from garden hose or connect to bulk supply tank (No float tank)
PRESSURE HOSE 3/8" x 50', 4000psi, 250° rated
GUN / WAND 48" molded insulator wand with nozzle holder and quick coupler
SOAP INJECTION Optional soap injection available
NOZZLE #4.5 (15°,40°) #4.0 (25° steam)
BURNER COIL Spiralast™ robotically fused ½" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation
BURNER/POWER Oil fired, 115v, Auto Ignition, Forced Draft, Fuel Filter, Fuel Solenoid
BURNER FUEL/CAP Diesel Fuel #1 or #2, Kerosene, or fuel oil, 18gal. – 454,000 Btu input
GENERATOR On-board 2900 watt, 115v, brushless, generator for auxiliary power
CONSTRUCTION Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall
coil end caps (stainless steel frame option available)
WHEELS Optional wheel kit available
WEIGHT/DIM. 588#, 51"x34"x41"

Specifications subject to change without notification and may vary due to ambient conditions – Battery not included

Featuring:

- ✓ Rugged Pro-Tect-It frame, with 4-point lifting or tie down eyes
 and hose reel mounting points, can be truck or trailer mounted or
 pulled/towed with the optional wheel kit
- ✓ **Super Duty Heating system** uses schedule 80 coil pipe, stainless steel and ceramic insulation combined with a proven 110 volt oil fired burner for trouble free and efficient heating
- ✓ Commercial/Industrial Engines Twin cylinder, overhead valve for reduced emissions and maintenance. Full pressure lubrication and oil filter for long life.

Options...

Hose Reel (AR425, AR100, AR150), Stainless frame option (HS208), Custom skid color (CTSKD), Wheel Kit 13" w/pull bar steering (AHB12), locking kit for wheels (AHB20), Trailer, Tank Skid, Down Stream Injection (AC340), Float Tank w/inlet injection (WT0SD), Winterizing Tank (AWTW5), Hour Meter (AM601), Hydro Vacuum wastewater recycle

TO:	
COMMENTS:	
YOUR PRICE:	
DISTRIBUTED BY:	Lynco Products Inc. # 114, 1220 - 28 STREET N.E
	CALGARY, AB T2A 6A2 403-250-3600 / 1-877-249-3600
	sales@lyncopro.com / www.lyncopro.com



